

TEST PORT >>>

(Sizes in mm)

ORDERING INFORMATION

TP 1 C 0100 AF ---- / d- KF H-

Description (产品类型)

TP : TEST PORT
(测试口)

Material (材质)

- 1 : SS304
(不锈钢304)
- 2 : SS304L
(不锈钢304L)
- 3 : SS316L
(不锈钢316L)

Coating Yes/No (是否喷涂)

- C : ETFE Coated (ETFE 喷涂)
- S : Stainless Steel Uncoated (不锈钢不喷涂)

Diameter: D (直径)

50mm ≤ D ≤ 3500mm

eg. 0100: Diameter 100mm (直径100mm)

Connection (连接形式)

- AF : Standard, SS304 Angle Flange, Tack Welded
(标准不锈钢304角钢法兰,点焊)
- AN: SS304 Angle Flange, Not Tack Welded
(不锈钢304角钢法兰,不点焊)
- PF : SS304 Flat Flange, Tack welded
(不锈钢304平板法兰,点焊)
- PN: SS304 Flat Flange, Not Tack Welded
(不锈钢304平板法兰,不点焊)
- KF : SS304 KF Flange, Fully Welded
(不锈钢304 KF 法兰, 满焊)
- SF : SS304 ISO Flange, Fully Welded
(不锈钢304 ISO 法兰, 满焊)
- XF : Customized Flange
(定制法兰)

Length: L (长度)

STD L : 150mm

eg. 0200: Length 200mm
(长度200mm)

Test Port Size: d (测试口尺寸)

- d1/4 : 1/4" d1 : 1"
- d3/8 : 3/8" d1.5 : 1.5"
- d1/2 : 1/2" d2 : 2"
- d3/4 : 3/4" d3 : 3"

Test Port Connection (测试口连接)

- KF : KF Flange
(KF 法兰)
- SF : ISO Flange
(ISO 法兰)
- BT : Bare Tube
(不锈钢不喷涂)
- MNPT : Male NPT Thread
(美标公螺纹)
- FNPT : Female NPT Thread (Welded MNPT+ PTFE Coupling)
(美标母螺纹 (公螺纹焊接+特氟龙母螺纹转接头))
- BSPM : Male NPT Thread
(国标公螺纹)
- BSPF : Female NPT Thread (Welded MNPT+ PTFE Coupling)
(国标母螺纹 (公螺纹焊接+特氟龙母螺纹转接头))
- SW : Compression Joint Connector
(卡套接头)
- VCRm : Male VCR
(VCR公头)
- VCRf : Female VCR
(VCR母头)
- XF : Customized Flange
(定制法兰)

Test Port Height: H (测试口高度)

- H30 : Test Port Height 30mm
(测试口高度30mm)
- H50 : Test Port Height 50mm
(测试口高度50mm)

